

NATIONAL PETROLEUM COMPANY- NPC

AMMAN JORDAN
Schedule of specifications and prices

NPC
شركة البترول الوطنية (م.ع.م)



MUD CHEMICALS

Tender No. 43/2025/S

Item No.	DESCRIPTIONS	UNIT	QTY	W/O CUSTOMS & TAXES	
				RISHA STORES	
				Unit price	Total Price
1	<u>CMC LV</u> : TECHNICAL GRADE LOW VISCOSITY CARBOXIMETHLYCELLULOSE IN GRANULAR FORM (1 TO 3 MM MAX DIE) FOR FILTRATION AND VISCOSITY CONTROL, FULLY CONFORMED TO API 13-A SPECIFICATION PACKED IN POLYPROPYLENE BAGS CONTAINING 25KG LOTS OF 40 BAGS TO BE STRAPPED AND WRAPPED ON PALLETS 2-WAY ENTRY EXPORT TYPE, WITH POLYETHYLENE COVER.	BG	440		
2	<u>FERRO CHROME LIGNOSULFONATE (FCL)</u> : BLENDED IN ONE BAG PACKED IN PAPER BAGS. CONTAINING 25KG BAGS TO BE OF 5-PLY INCLUDING ONE POLYETHYLENE LINER, LOTS OF 40 BAGS POLYETHYLENE COVER TO BE STRAPPED AND RAPPED ON PALLETS OF HARD WOOD TWO-WAY ENTRY EXPORTS TYPE POLYETHYLENE COVER.	BG	80		
3	<u>SODA ASH</u> : SODIUM CARBONATE (Na ₂ CO ₃) PH>10.5 PACKED IN POLYPROPYLENE BAGS. CONTAINING 25 KG BAGS LOTS OF 20 BAGS POLYETHYLENE COVER TO BE STRAPPED AND RAPPED ON PALLETS OF HARD WOOD TWO-WAY ENTRY EXPORT TYPE POLYETHYLENE COVER.	BG	40		
4	<u>CEPACK-LV</u> : POLYANIONIC CELLULOSE OFF WHITE POWDER FORM, ADDITIVE DRILLING FLUID, GRANULAR HIGH DENSITY ORIENTED AND CROSS-LAMINATED INNER POLY-ETHYLENE RESIN LINER WITH A WEIGHT RANGE OF 15#24 G/M2 4TH PLY 70 G/G/M2 .LOW VISCOSTY GRADE FOR USED FOR FILTRATIN CONTROL IN DRILLING MUD, DRY, FREE-FLOWING GRANULATED POWDER, SALT AND FRESH WATER-SOLUBLE POLYANIONIC CELLOSE POLYMER, SALT -FREE AND SHALL NOT CONTAIN ANY OTHER POLYSACCHARIDES ,THE PRODUCT IS RESISTANT TO MICRO-ORGANISMS ,DISPRESS RAPIDLY IN FRESH WATER, BRACKISH WATER. SALT SATURATED DRILLING FLUIDS, IT PROVIDES FILTRATION CONTROL AND FORMS A THIN FILTER CAKE WITH LOW PERMEABILITY INHIBITS SHALE, CLAY AND STABILIZES RHEOLOGY, CHEMICAL AND PHYSICAL SPECIFICATIONS: APPEARANCE;; WHITE OR TAN GRANULAR POWDER MOISTURE CONTENT:10%, MAXIMUM SODIUM CHLORIDE CONTENT (1% SOLUTION IN DI WATER) ; 0.02% WT MAXIMUM, STABLE AT MINIMUM 350 F DEY. TEMP. PACKED IN 25KG OR 22.7KG (EACH TO BE OF 5-PLY PAPER BAGS). CONSTRUCTION WITH INNER AND OUTER POLYTHENE COATED LOTS OF 40 BG TO BE STRUPPED AND WRAPPED ON PALLETS CONSTRUCTED OF HARD WOOD TWO-WAY ENTRY EXPORT TYPE POLYETHYLENE COVER.	BG	400		
				TOTAL	

CURRENCY:

DELIVERY PERIOD :

VALIDITY :

MANUFACTURER:

ORIGIN OF GOODS :

SPECIAL CONDITIONS:

NOTES:

ALL COLUMNS AND BLANK MUST BE FILLED IN AND IT'S THE NPC CHOICE TO CHOOSE THE PRICE WHICH SUITS IT'S REQUIRMENT

ORIGINATOR:	issa makhamreh	SIGNATURE		DATE: 30/10/2025
HEAD OF DIVISION:	issa makhamreh	SIGNATURE		DATE: 30/10/2025
DEPARTMENT MANAGER:	Eng.ghassan al kiki	SIGNATURE		DATE: 30/10/2025



Notes: -

- 1. BIDDERS MUST COMPLY TO THE MATERIAL'S TECHNICAL SPECIFICATION IN THE ATTACHED TENDER DOCUMENTS.**
- 2. SPECIFICATIONS OF OFFERED MATERIALS MUST CONFORM TO API OR OCMA SPECIFICATIONS.**
- 3. TWO SEPARATE SAMPLES OF EACH ITEM ½ KG EACH "LABELED AND SIGNED BY THE MANUFACTURER MUST BE SUBMITTED WITH OFFERS. OFFERS WITHOUT SAMPLES WILL BE REJECTED.**
- 4. ONE SAMPLE IS TO BE USED FOR LAB TEST; THE OTHER WILL BE KEPT IN NPC'S OFFICE FOR COMPARISON PURPOSES WITH THE AWARDED SUPPLIED MATERIALS.**
- 5. NPC HAS THE RIGHT TO LABORATORY TEST SUPPLIED SAMPLES IN ORDER TO CHOOSE THE MOST SUITABLE OFFER TO ITS NEEDS.**
- 6. LAB TEST RESULTS OF THE SUPPLIED SAMPLES MUST CONFORM TO THE SPECIFICATION STATED IN THE OFFER.**
- 7. THE SPECIFICATION OF SUPPLIED MATERIALS MUST CONFORM TO THE SAMPLES SPECIFICATIONS "SUBMITTED WITH THE OFFERS ". OTHERWISE NPC HAS THE RIGHT TO REJECT THE SUPPLIED MATERIALS.**
- 8. ORIGIN OF THE GOODS AND MANUFACTURER MUST BE LISTED IN THE OFFER.**
- 9. PACKAGING MUST COMPLY WITH THE REQUIREMENTS OF THE NPC.**
- 10. MARKING : EACH BAG SHOULD HAVE CLEAR LEGIBLE MARKING AS GIVEN BELOW:**
 - Name of the product.
 - Name of the supplier/manufacturer
 - Date/Month/Year of Manufacturing
 - Supply order No. against which the present supply is made